

**RAC EXPORTS,****HIGH-QUALITY INSTRUMENTS****Features**

- ▣ Large 3 1/2 digital LCD display with function indication
- ▣ Wider measuring range with high accuracy
- ▣ Data hold function
- ▣ Max hold function

**Specifications**

- ▣ Two mode provide 2.5dB or 3.5dB accuracy
- ▣ A and C weighting, high and low measuring ranges: low (35-100dB), High ( 65 to 130dB)
- ▣ 0.1dB resolution
- ▣ Fast / slow response
- ▣ Data HOLD and MAX hold
- ▣ Large 3 1/2 digital
- ▣ Built-in calibration check (94dB)
- ▣ Complete with 9V battery and carrying case
- ▣ Dimensions: 215 x 63.8 x 40mm/250g

Function	Range (Freq Range: 31.5Hz to 8KHz)	Resolution	Accuracy
Sound Level (Frequency Weighting: A,C)	A Lo (Low) - Weighting: 35dB~100dB	0.1dB	+ 3.5 dB at 94dB sound level, 1kHz sine wave
	A Hi (High) - Weighting: 65dB~130dB		
	C Lo (Low) - Weighting: 35dB~100dB		
	C Hi (High) - Weighting: 65dB~130dB		